

More power for your diagnosis with the DIAGNOSTIC INTERFACE WOW! LOOQER



Benefit from the multi-brand diagnostic interface WOW! LOOQER

(Art. Nr. W072 003 000) with full functionality and the newest technology.



- **CAN-FD** for fast CAN bus communication in future vehicle technologies
- DoIP Diagnostics over Internet Protocol (ISO 13400-2) for reading the latest vehicle technology
- **Pass Thru** J2534 compatible VCI hardware for use with OE diagnostic software
- WiFi and Bluetooth technology



Less is more

Small diagnostic interface on the market with full functionality and the latest technology

- Small, handy, light, robust, workshop-ready
- Use as you need it: as a small, wireless dongle or via enclosed cable

The key to successful diagnostics on Security Gateway protected vehicles Simple. Fast. Save.

- Manufacturer-independent and multi-brand work on vehicles that are secured with security gateway systems
- Familiar and standardised user interface with familiar terms in the LOOQIT software
- One-time authentication of just one authorised person and simple addition of further users

Relevant data with the Flightrecorder Connect, drive off, record mobile data, evaluate later

- Save pre-selected data on the internal hard drive during the journey without any further input device
- Later analyse everything in detail with the WOW! software
- Without a co-driver, without cables, without problems
- Save time and money



For further information please contact your WOW! or Würth sales person or visit **www.wow-portal.com/diagnostics**





More power for your diagnosis with the **DIAGNOSTIC INTERFACE WOW! LOOQER**

COMPARISON OVERVIEW





| | LOOQER The new diagnostic interface with the newest technology Art. no. W072 003 000 | SNOOPER+ The long-standing mobile and reliable diagnostic interface Art. no. W072 700 100 |
|---|---|---|
| Flightrecorder | | |
| Access to Security Gateway protected vehicles | ~ | Image: A set of the set of the |
| Security Gateway Premium | | × |
| Power supply | 12V DC or 24V DC, tolerance 6V-36V | 12V DC, tolerance 6-35V |
| Rubberised casing | | Image: A set of the set of the |
| DoIP – Diagnostics over Internet Protocol | ~ | Possible via an additional adapter (except Mercedes-Benz) |
| CAN-FD technology | Image: A set of the set of the | × |
| Pass-Thru J253 WiFi | | × |
| WiFi | | × |
| Exchangeable OBD plug head | Image: A set of the set of the | × |
| Protection class IP44 (splash water protected) | Image: A set of the set of the | × |
| Bluetooth technology | 2.1 + EDR/BLE, range 30 m | 2.1 |
| USB connection | USB-C | USB-2 |
| Weight | 0,132 kg | 0,480 kg |



For further information please contact your WOW! or Würth sales person or visit **www.wow-portal.com/diagnostics**

